

# JVS-N98-X3

## 3MP Dual-Lens Full-Color Wi-Fi PTZ AI Camera



### Features

- Binocular Zoom Lens, 3MP Ultra-clear Image Quality;
- 18x LED lights, Dual Light Sources for Supplementary Lighting;
- Built-in speaker + MIC, Support Volume Adjustment, Two-way Voice Intercom;
- Support Warm Light, Infrared, Intelligent Dual Light, Sound and Light Warning Modes;
- Support Wi-Fi Connection, Wired Connection and AP Connection;
- Support Humanoid Detection, Humanoid Tracking;
- Support SD Card, Maximum Support 512G;
- Support Region Intrusion, Line Crossing, Leave Detection, Road Occupation;

### Specifications

Video	
Image Sensor	1/2.9" CMOS Sensor
Max Resolution	2304x1296
Effective Pixels	3.0MP
Compression Standard	H.264/H.265(Default)
Frame Rate	25fps
Bitrate	Main Stream: 128Kbps ~ 4096Kbps Sub Stream: 68Kbps~1024Kbps
SNR (dB)	50dB
Min. Illumination	0Lux (light ON)
Lens	

<b>Interface Type</b>	M12
<b>Lens</b>	3.6-8mm
<b>FOV</b>	Wide Angle: H 78.5°, V 42.8°, D 92.6° Telephoto: H 19.4°, V 10.9°, D 21.8°
<b>Function</b>	
<b>Audio Codec</b>	G.711U/G.711A (Default)
<b>Exposure Control</b>	Auto
<b>White Balance</b>	Auto
<b>Gain Control</b>	Auto
<b>Digital 3D Noise Reduction</b>	Support
<b>OSD Information Setting</b>	Large Font OSD, OSD Flashing on Alarm, OSD Position Settings
<b>SNTP</b>	Support
<b>Schedule Reboot</b>	Support
<b>Smart Defog</b>	Support
<b>Motion Detection</b>	Support Humanoid Detection
<b>Image Setting</b>	Support Saturation, Brightness, Contrast, Sharpness Adjustment
<b>Image Style</b>	Standard, Soft, Transparent
<b>Day and Night Function</b>	Automatic Switching, Timing Switching, Day Mode, Night Mode
<b>Privacy Mask</b>	A Single Screen Supports 8 Privacy Masks, And Supports Up To 24 Masking Areas
<b>Night Vision Optimization</b>	Support
<b>DWDR</b>	Support
<b>Screen Settings</b>	Screen Mirroring, Screen Flipping
<b>IP Adaptation</b>	Support Automatic Adaptation of IP Address
<b>Intelligent Analysis</b>	Support Region Intrusion, Line Crossing, Leave Detection, Road Occupation
<b>Alarm Method</b>	Email Alarm, Client Alarm
<b>Remote Operation</b>	System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis
<b>Audio Function</b>	Built-in Mic and Speaker
<b>SD Card</b>	Support ( 512G )
<b>Reset Button</b>	Support
<b>Network</b>	
<b>Ethernet</b>	10/100Mbps Ethernet
<b>Stream</b>	2x Streams
<b>Network Protocols</b>	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
<b>ONVIF</b>	Standard ONVIF
<b>Network Transmission</b>	CloudSEE 2.0
<b>Browser</b>	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
<b>User</b>	Up to 13 Users
<b>App</b>	Support iOS/Android
<b>General</b>	
<b>Lights</b>	12 White LEDs + 6 IR LEDs
<b>Fill Light Distance</b>	White LED:50 Meters IR LED:40 Meters
<b>Waterproof Level</b>	IP66
<b>Power Supply</b>	DC12V/2A
<b>Power Consumption</b>	<6W (During Day); <15W (At Night)
<b>Working Temperature</b>	-30℃~60℃(-22℉~140℉)
<b>Working Humidity</b>	10% ~ 90% Rh
<b>Color/Material</b>	White/Black; Plastic/Front Shell Aluminum Alloy
<b>Dimensions (WxHxD)</b>	160x257x187mm
<b>Weight</b>	770g
<b>Installation Method</b>	Wall Or Ceiling Mount