


JVS-ND7608-HP

8CH H.265 1 SATA NVR



Key Features

- Adopt the new Vstar GUI , easy to operate and run smoothly
- Support intelligent coding VSMart, greatly reducing storage space
- Improved compatibility for hard disks, and up to 10TB
- Supports multiple intelligent analyses such as motion detection, regional intrusion, tripwire detection, passenger flow statistics, scene changes, and occlusion alarms;
- Support the preview, storage and playback of 4K HD network video;
- Support built-in speakers, realize real-time monitoring of video recording, support voice alarm;

Specifications

| Model | JVS-ND7608-HP |
|----------------------------------|---|
| Video and Audio | |
| IP Camera Input | 8Channel |
| Audio Input/ Output | IPC Audio input/Audio output through HDMI |
| Built-in Speaker | Support |
| Bandwidth I/O | 80Mbps/80Mbps |
| Display | |
| Interface | 1 HDMI, 1 VGA |
| Resolution | HDMI: 3840×2160@30Hz/2560×1440@30Hz/1920×1080/1440×900/1280×1024/1280×720/1024×768 VGA: 1920×1080,1440×900,1280×1024,1280×720,1024×768 |
| Max Decoding | 1ch 4K 15fps; 8ch@ 5.0MP/4.0MP/1080P/960P/720P 25fps |
| Multi-screen Display | 1/4/5/6/7/8/9 |
| OSD | Camera Name & Time, Recording, Alarm Detecting, Remote connection, Volume, Channel Number |
| Recording | |
| Compression | H.265/H.264 |
| Resolution | 1Ch 4K; 8Ch 5.0MP/4.0MP/1080P/960P/720P |
| Record Mode | Manual, Schedule, MD |
| Video Detection and Alarm | |
| Trigger Events | Recording, Snapshot, PTZ, Voice, E-mail, Client, Buzzer |
| Video Detection | Motion Detection, No Video Detection |
| Playback and Backup | |
| Sync Playback | 1ch 4K,1ch 5.0MP, 1ch 4.0MP, 1ch 3.0MP, 2ch 1080P |
| Search Mode | Channel number / recording type / date |
| Playback Function | Day View, Hour View, Back Step, Rewind, Pause, Play, Fast Forward, Slow, Step, Full Screen, Snap, Sound On/Off, Zoom |
| Backup Mode | FAT32 USB Device/Network |
| Network | |
| Interface | 1 RJ-45 port (10/100Mbps) |
| Network Function | TCP/IP, DHCP, UDP, SMTP, NTP |
| Smart Phone | iPhone, Android |
| Interoperability | ONVIF 2.4 |
| Storage | |
| SATA | 1 SATA interfaces |
| Capacity | up to 10TB |
| General | |
| Power Supply | DC 12V |
| Consumption | ≤ 10 W (Without HDD) |
| Working Temperature | -10°C~ 55°C |
| Working Humidity | 10 % ~ 90 % |
| Dimensions | 260X47.5X225mm |
| Weight | ≤ 1.0kg (Without HDD) |

Description

